

- Available in Double 4.5" and Double 4.5" Dutchlap profile.
- Engineered for stronger performance.
- .044" premium thick vinyl for outstanding strength and durability.
- Gracious traditional appeal.
- Timeless beauty.
- Lifetime warranty.
- Lifetime fade warranty.
- Premium panel.
- Look of freshly painted wood.
- Combines classic good looks with modern convenience and performance.
- Provides you with a lifetime of protection for your investment as well as with peace of mind for as long as you own your home.
- Engineered for stronger performance.
- A Sleek Silhouette
- Won't chip, peel, or crack.

Pinehurst



Manufacturer

Materials to be supplied by Continental Manufacturing LLC, 800 S Wellington, Richmond, MO 64085.

Materials

All of the vinyl siding shall be extruded Poly Vinyl Chloride (PVC) and shall conform to the following requirements established by ASTM Specifications D 3679, developed in cooperation with the industry and published by the American Society for Testing and Materials.

Typical Compound Properties

Tensile Strength: ASTM D638 6,040 psi
 Tensile Modulus: ASTM D638 365,000 psi
 Flexural Strength: ASTM D790 11,500 psi
 Flexural Modulus: ASTM D790 410,000 psi
 Izod 73°F Method A 17.0 ft-lb/in

VSI Flammability

Burn Length (0.040 in Bar) ASTM D635 0* IN. Burn Time (0.040 in Bar) ASTM D635 0* Sec
 Drop Dart Impact Resistance Procedure A, 73° F ASTM D4226 1.9 in-lb/mil
 Drop Dart Impact Resistance Procedure B, 73° F ASTM D4226 4.0 in-lb/mil
 Vulcanizate Properties Hardness Instantaneous, D ASTM D2240 83
 Thermal Properties HDT Unannealed, 264 psi ASTM D648 162 °F
 Coeff of Linear Thermal Expansion ASTM D696 3.6EO in/in/°F
 Gloss: plus or minus 5 units, ASTM D3679
 Surface Distortion: No Distortion at 105°F, ASTM D3679
 Weatherability: No surface or structural defects when tested as per ASTM D3679

Siding Dimensions and Description

Pinehurst D4.5 and D4.5 Dutchlap, horizontal siding panel, 9 in. wide exposure configured as two 4.5" in. panels, 12', 16'8" & 29' lengths.

Thickness 0.044 in. ±0.002 in.

Embossed Wood Grain: Color to match the samples provided.

Interlock: Siding panels are made with post form style lock with positive interlock.

Both ends of the panel are factory cut and notched for overlap.

Weep holes: Small holes under the bottom butt prevent vapor build up and allow accumulated moisture to escape.